



PORTABLE USB CO₂,TEMP,RH MONITOR/DATALOGGER



Backlight function is optional



MIC Portable CO₂/VOC/CO meter connects with any power bank unit

Parameters	Air, DP, WB Temp. ,RH%.CO ₂ 98132SD
TWA.STEL	N/A
cfm/p, Ips%	N/A
Interface	USB-Off ling logging memory 32,000 points 
Meas.range	0-9,999ppm (Resolution 1ppm)
Temp.range	10.0~50.0°C
Resolution	1ppm,0.1°C/°F,0.1%RH
RH % Range	10%~90%RH
Accuracy	±1.0°C(Temperature) ±5% RH (At 25C) ± 75ppm ±5% of rdg (CO ₂) 0~5000ppm , others unspecified

FEATURES :

- Cost effective portable selectable CO₂,Temp. RH (98132S.98132SD.98132SP)
- Basic model features on line (Real time) datalogging CO₂.Temp.RH w/free software(98132S model only)
- Meter stands alone (off line) stores up to 32,000 points (CO₂.Temp.RH) (Model 98132SD only)
- Measure from 0ppm up to 9999ppm CO₂ concentration with high resolution 1ppm
- Temp. RH% display interchangeably (98132S.98132SD.98132SP).
- Calculate dew point , wet bulb temperature in seconds(98132S.98132SD.98132SP)
- Pressure display (300~1100hpa) and adjustable to compensate CO₂ reading(98132SP)
- Manual calibration CO₂ (with 400ppm environment)
- Triple LCD display large size 44x33mm.
- High alarm threshold setting. Press PWR button to turn off beeper.
- HOLD function: Press button to freeze readings
- Maximum/Minimum : Record since powered on
- Display TWA.STEL and vent rate (cfm/p or lps%) in second (98132SP)
- Powered by AAA x6 pcs batteries for short time measurement.
- Using power charger for portable around measurement
- Recommend to use optional adaptor for long time monitoring or checking .
- Battery life is about 20~ 24 hours , Battery low indication function.
- Auto power off in 15 minutes for saving battery life and is disablement.

Supplied with :

Meter x1 , Batteries AAA x6 , Operation manual x 1 , Pouch x1 .

Optional: AC/DC adaptor. Or backlight function

	98132SR	98132S	98132SP
Parameters	CO ₂ , Air ,RH%.Temp.	CO ₂ , RH% Air, DP,WB Temp.	CO ₂ , Air,DP,WB Temp. RH%.Pressure
TWA.STEL		N/A	YES
cfm/p, lps%		N/A	YES
Interface	N/A	USB-On ling logging	N/A
Pressure correction		N/A	300~1100hpa/mbar
Meas.range	0-9,999ppm (Resolution 1ppm)		
Temp.range	10.0~50.0°C		
Resolution	1ppm,0.1°C /°F	1ppm,0.1°C /°F,0.1%RH	
RH % Range	10%~90%RH		
Accuracy	±1.0°C (Temperature) ±5% RH (At 25C) ± 75ppm ±5% of rdg (CO ₂) 0~5000ppm , others unspecified		