

TES

Reliable in Quality



TES-1306 K/J Dual Channels Thermometer

- K/J type thermocouple Input
- Multi-Channels Scanner T1→ T2→T1-T2
- MAX/MIN/Relative Reading/Data Hold
- Touch-tone button easy to operate



TES-1306 K/J Thermometer



Features:

- K/J Type thermocouple input
- Auto ranging
- Data Hold
- Maximum / Minimum reading
- Relative reading
- Multi-channels scanner (T1 →T2→T1-T2)

Specification

Measuring Range	Type K : -200°C to 1370°C (-328°F to 1999°F) Type J : -200°C to 760°C(-328°F to 1400°F)
Accuracy	(-200°C~ 0°C) (±0.2%rdg+ 1°C) (-328°F ~ 32°F) (±0.2%rdg+ 2°F) (0°C~ 200°C) (±0.1%rdg+0.8°C) (32°F~ 392°F) (±0.1%rdg+1.6°F) (200°C~1370°C) (±0.2%rdg+ 2°C) (392°F ~2498°F) (±0.2%rdg+ 3°F)
Resolution	-200°C~ 200°C (0.1°C) 200°C~1370°C (1°C) -328°F~ 392°F (0.2°F) 392°F~2498°F (2°F)
Input Protection	60VDC/24Vrms
Power Source	One 9V battery. 006p or NEDA1604 or IEC6F22
Battery Life	Approx. 100hr
Operating / Storage Condition	0°C to 40°C (32°F to 104°F)below 80% RH. -10°C to 60°C (14°F to 140°F) below 70% RH.
Dimensions	135(L)×72(W)×31(H)mm
Weight	Approx. 235g with battery

Optional Temperature Probes K(CA) Type Thermocouple

Model	Testing Range	Description
TP-K01 Bead	-50°C-200°C/-58°F-392°F	for general condition, especially for complex and place hard to reach.
TP-K02 Immersion	-50°C-1000°C/-58°F-1832°F	for temperature measurement of liuqid or gels.
TP-K03 Surface	-50°C-750°C/-58°F-1382°F	for surface measurement.



TES ELECTRICAL ELECTRONIC CORP.

No. 57 Jen-Ai Road, Sec.2, Taipei , Taiwan
Tel: (02) 2393-9142 Chen Tes Fax: 886-2-2395-9146
E-Mail Address: tes@ms9.hinet.net
home page:http://www.tes.com.tw